



TYPICAL CROSS SECTION
TYPICAL SIDEWALK

NOTES:

1. TYPICAL SIDEWALK SHALL BE 4" THICK. SIDEWALK THROUGH DRIVEWAYS SHALL BE 5" THICK, OR THE DRIVEWAY THICKNESS, WHICHEVER IS GREATER. SIDEWALKS THROUGH ALLEYS SHALL BE 7" THICK.
2. 1/2" EXPANSION MATERIAL REQUIRED AT PROPERTY LINE AND DRIVEWAYS AND EACH 75 FT. INCREMENT ALONG LENGTH OF SIDEWALK.
3. SIDEWALK CROSSING DRIVEWAY MAY HAVE A MAX. 4% CROSS SLOPE AS APPROVED WHERE GRADE RESTRICTIONS EXIST. NORMAL SIDEWALK CROSS-SLOPE SHALL TRANSITION TO SPECIAL SLOPE WITHIN 16-FOOT LENGTH.
4. MINIMUM WIDTH IS 4 FT FOR RESIDENTIAL AND 5 FT FOR COMMERCIAL AREAS.

FILE NO.: 2700-112	CEDAR RAPIDS METROPOLITAN AREA STANDARD DETAILS FOR PUBLIC IMPROVEMENTS	
APPROVAL DATE: APRIL 2003	TYPICAL SIDEWALK AND RIGHT-OF-WAY GRADING	
REVISION NO.: 1		NO.
REVISION DATE: APRIL 2003		2700-112